

sensorProbe8-X20



sensorProbe8-X20

At the core of the sensorProbe8-X20 is the sensorProbe8, which is then married with the 20 Dry Contact System. This offers support for remote monitoring and management of a wide range of external devices.

The sensorProbe8-X20 system enables connection and monitoring of devices like HVAC systems, Security Equipment, UPS, Generators, Industrial Equipment and much more.

Introducing the sensorProbe8-X20

The sensorProbe8 embedded web server makes the addition of these devices easy. The sensorProbe8-X20 comes with 8 autoSense Intelligent sensor ports, for connecting a wide range of our intelligent sensors.

An additional 20x 2-wire dry contact ports are provided giving a total of up to 28 dry contact ports. The specially designed 2 wire dry contact ports are easy to use and allow you to make your own dry contact cables quickly. The sensorProbe8-X20 is a completely embedded host. It is equipped with a TCP/IP stack, internal web Server, e-mail and Full SNMP functionality.



sensorProbe8-X20 Monitoring System

sensorProbe8-X20 safeguards your infrastructure, resources and investment from external disaster before it happens.

sensorProbe8-X20's Main Features

- Fully embedded TCP / IP and Web Server
- Built-in notification Suite
- 8 autoSense ports for AKCP sensors
- Web-Based Interface for easy configuration and monitoring
- Login for User and Administrator for increased security
- Battery backed time of day clock for an accurate system date and time
- A standalone product without any external hardware and software dependencies
- Microcode firmware updates over the Internet
- Customized color configuration for displaying alerts
- Network Management System integration
- An additional 20, 2 wire dry contact input ports are provided, giving a total of up to 28 dry contact ports

sensorProbe8-X20 Port Configuration



Industry Certifications & Network Management Systems

AKCP offers NMS Integration for leading network management systems such as:

- AdRem NetCrunch
- IBM Tivoli
- SiteScope
- Quest Software – Big Brother
- Loriot Pro
- Somis WebNM and Denika
- Castle Rock
- Logalot
- WhatsUp Gold
- HP OpenView
- MRTG
- Computer Associates Unicenter TNG



Support and Warranty

- **1 year Limited Warranty, Optional 2 Year Warranty.**
- **Unlimited Lifetime Support.**
- **Free Firmware Updates.**
- **Full, Easy to Follow Documentation.**



Technical Specifications

Dimension Size 18" x 5" x 1.65" 1U Rack Mount Standard Weight 2.2 pounds	Network Interface Standard 10 Base-T Ethernet RJ-45	Mounting 1U Rack mount bracket included
Power Requirements Voltage 7.0 – 9 v Current >= 3 Amp	Status Indication LED indication for Power LED for Network Connectivity LED for sensor online and threshold status	Output Configurable output signals (0VDC/5VDC) on any of the 8 RJ-45 sensor ports
Inputs 8 RJ-45 ports for connecting AKCP sensors 20, 2 wire dry contacts. Input only up to 5VDC and up to 40VDC in opto isolated mode using internal jumper setting.	Operating Environment Temp : Min. -35° C - Max. +55° C Humidity : Min. 20% - Max. 80% (Non-Condensing)	Components Manufactured using highly integrated, low power surface mount technology to ensure long term reliability.

Power Consumption

Typical 1.90 Watt, 0.21A



SAVE PAPER. SAVE TREES.
SAVE THE Planet.



2F Republic Glass Bldg., 196 Salcedo St., Legaspi Village, Makati City
T: 813-4162/63 F: 812-9310 E: info@mannasoft.com
www.mannasoft.com